

# **Silkolene**<sup>®</sup>

## **SILKOLENE PRO CHAIN**

**Fully synthetic racing chain lubricant**

### **Description**

SILKOLENE PRO CHAIN is a clear thin film, synthetic chain lubricant designed for maximum protection and minimum fling off in racing applications. SILKOLENE PRO CHAIN incorporates a micronised laminar solid lubricant which combined with advanced synthetics gives outstanding boundary lubrication leading to lower friction and reduced wear. Suitable for all chains including “O”, “X” and Z ring types.

### **Application**

- Ensure chain is clean and dry prior to applying SILKOLENE PRO CHAIN Lube
- We recommend the use of SILKOLENE BRAKE AND CHAIN CLEANER prior to use
- Shake can well before application
- Apply sparingly to the whole length of the inside of the chain
- Leave for a minimum of 15 minutes before use
- Wipe away excess
- Following application, invert the can and spray for a few seconds to avoid clogging the nozzle

### **Advantages / Benefits**

- Excellent wear and shock loading protection even with the thin film, low friction oil film
- Excellent resistance to high speed fling off
- Resistant to water wash off
- Penetrates and evaporates quickly with excellent film forming properties
- Resists dirt adhesion
- Works at high temperature / high load race conditions
- Good corrosion protection

Updated 25/01/2022 ABUK



Health, Safety and Environment - information is provided for products in the relevant Safety Data Sheet. This provides guidance on potential hazards, precautions and first-aid measures, together with environmental effects and disposal of used products. While the information and figures given here are typical of current production and conform to specification, minor variations may occur. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of the products