

TITAN SINTOPOID LS SAE 75W-140

Premium Performance Gear Oil formulated with fully-synthetic base oils. Suitable for axle and transfer gearboxes with and without limited slip differential, also as fill for life fluid according to manufacturer.

Description

TITAN SINTOPOID LS SAE 75W-140 is a fully-synthetic, high-performance gear oil for the use in highly loaded passenger car axle and transfer gear-boxes equipped with either conventional or limited slip differentials.

Application

TITAN SINTOPOID LS SAE 75W-140 complies with the wear protection requirements of API GL-5 and is suitable for the use in hypoid drives even under highest stress. Due to the additive chemistry used with LS-capable components (Limited Slip) the product can be used in both conventional and limited slip differentials. TITAN SINTOPOID LS SAE 75W-140 can be used in passenger cars where a lubricant of this quality is specified. TITAN SINTOPOID LS SAE 75W-140 is miscible and compatible with conventional branded gear oils. However, mixing with other gear oils should be avoided in order to fully utilize the product's benefits. A complete oil change is recommended when converting to TITAN SINTOPOID LS SAE 75W-140. For information on product safety and proper disposal please refer to the latest Material Safety Data Sheet.

NOTE - Homogenize product before use.

Advantages/Benefits

- Excellent resistance against shear and ageing
- Allows increased drain intervals
- Particularly effective resistance to highest loads
- Less deposits due to excellent high temperature stability
- Outstanding wear protection even under severe conditions
- Good low temperature properties

Specifications

- API GL-5

Approvals

- -

FUCHS Recommendations

- BMW 83 22 2 282 583
- BMW 83 22 9 407 870
- CHRYSLER MS-8985
- FORD WSL-M2C192-A
- GM 12346140
- JOHN DEERE JDM J11G
- SCANIA STO 1:0

PI60248e, PMA, 23.02.2021, Page 1

TYPICAL CHARACTERISTICS

Density at 15 °C	DIN 51757	0.814 g/ml
SAE class	SAE J300	75W-140
Kinematic Viscosity at 40°C	DIN 51562-1	170 mm ² /s
Kinematic Viscosity at 100°C	DIN 51562-1	25 mm ² /s
Viscosity index	DIN ISO 2909	177
Pourpoint	DIN ISO 3016	-48 °C
Product dyeing	DIN 10964	none

PI60248e, PMA, 23.02.2021, Page 2

FUCHS LUBRICANTS (UK) PLC
New Century Street, Hanley
GB-Stoke-on-Trent, Staffordshire, ST1 5HU

Tel +44-1782 -20 37 00
Fax +44-1782 -20 20 73
contact-uk@fuchs-oil.com



Health, Safety and Environment - information is provided for products in the relevant Safety Data Sheet. This provides guidance on potential hazards, precautions and first-aid measures, together with environmental effects and disposal of used products.

While the information and figures given here are typical of current production and conform to specification, minor variations may occur. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of the products